

LIFTING INNOVATION

## C5000-C6000

The multi-directional forklift designed for the safe, space saving and productive handling of long and bulky loads.










REF.	DESCRIPTION	C5000	C6000
1a	Standard Lift Height	159″	
1b	Free Lift Height	0"	
2	Height Mast Closed	104"	
3	Max. (Mast Raised)	188″	
4	Overall Length	75"	89″
5	Mast Travel	33½"	47½"
6	Ground Clearance Under Mast	6"	
7	Ground Clearance to Wheelbase Center	5"	
8	Height Over Cab or of Overhead Guard	92"	
9	Width	76"	
10	Outside Spread of Fork Arms	47"	
11	Track Front	68"	
12	Frame Opening	48"	
13	Load Center Distance	24"	
14	Overhang Front	8"	
15	Wheel Base	60"	74"
16	Overhang Back	7"	
17	Length from Face of Fork	43½"	
18	Approach Angle	45°	
19	Ramp Angle	17°	
20	Departure Angle	45°	
21	Forward Tilt	2°	
22	Backward Tilt	4°	
23	Minimum Outside Radius	75″	87"
24	Platform Height	191/2"	
25	Platform Length	31½"	451⁄4"
Α	Capacity	5000 lbs	6000 lbs
В	Unladen Weight	10,350 lbs	10,800 lbs
С	Maximum Ground Speed	9 mph	
D	Gradeability	10%	
Е	Kubota V1505-T Diesel / GM 3L Tier 4 LPG	32 HP/ 65 HP	
F	Electrics	12 Volt	
G	Fork Sections 13/4" x 6" x	31½"	451/4"
Н	16 x 7 - 10.5 Front Tire	OD 16"/ Width 7"	
- 1	23 x 10 - 12 Rear Tire	OD 23"/ Width 10"	
J	Standard Color	Green and Gray	
K	Suspension Seat	KAB Model 211	


European Patent No. 2167416; Brazilian Patent No. P10811954-6; Australian Patent No. 2008253242


## Features Include:

- Rubber Mounted Half Open Cabin
- Multi-Directional Operation
- 3 Wheel Hydrostatic Drive
- Load Sensing Steering
- 4 Way Lever Positioning of Wheels
- Hydraulic Oil Cooler


## Distributed by:







FRONTAL MODE



303 Concord Street Greensboro North Carolina 27406

Toll Free: 1-877 COMBI 56 Tel: 336-378-8884 info@combilift.com

Combilift has a policy of continuous product development and reserves the right to alter specifications without prior notice. Specifications and/or dimensions may vary from those illustrated in some countries.